



Alloy

GNSS REFERENCE RECEIVER

THE FUTURE OF GNSS IS HERE

Trimble's all-new Alloy GNSS receiver offers powerful performance with the latest GNSS technology in a sleek new design that is easy and intuitive to use. Whether you need GNSS for campaign work or in permanent installations, the flexible configuration delivers reliable, robust data when and where you need it.

MODERNISED GNSS TRACKING

Using powerful Trimble 360 receiver technology in combination with dual Trimble Maxwell™ 7 chipsets, the Alloy GNSS receiver supports all known and planned GNSS constellations, ensuring your GNSS data is robust and reliable.

INTELLIGENT DESIGN

Review Key Info at a Glance

With a four-line angled display you can read all important information such as satellite tracking, position solution type, data logging, IP address, Wi-Fi®, firmware information and battery status right on the home screen. Set-up and verifying status information is now quick and easy.

Plug in and get to work

Multiple ports are easily accessible without the need for adaptors in a configuration that makes it simple to plug in a variety of external sensors and antennas.

Power when you need it

Alloy provides the most robust power options for any GNSS system. Featuring multiple power inputs with dual hot-swappable batteries, power over Ethernet, and advanced power management features, the Trimble Alloy GNSS receiver is ideal for any GNSS base station deployment.

Stackable Design

With a versatile, stackable design the Alloy GNSS receiver is built with a lightweight rugged aluminum alloy chassis which features IP68 certification. When you need to organise multiple units for deployment, simply stack and prep.

CONFIGURABLE ALERTS 24/7

Using Trimble Sentry™ technology, you can easily configure alerts that will automatically inform you of any changes to the position, data logging, configuration, tracking, power, communications, and system access events. Combined with advanced security measures such as IP filtering and multi-level user access, Trimble Sentry ensures continued operation of your Trimble Alloy GNSS receiver.

TRIMBLE RTX ON BOARD

The Alloy GNSS receiver is available with Trimble RTX™ advanced positioning technology allowing for rapid real-time network coordination. Whether this is for base station deployment or monitoring, Trimble RTX remains locked onto your real world absolute position.

COMMUNICATION

The Trimble Alloy GNSS receiver supports a wide range of communication protocols including Ethernet (IPv4 / IPv6), Bluetooth®, and Wi-Fi for flexible easy access via the built-in multi-language web interface and mini-web interface for mobile devices.

DATA

Storage

The Alloy GNSS receiver is able to store more data in less space by using specialised compression formats. Up to twelve independent high-rate data logging sessions can be stored internally, and using USB storage you can be sure the data you collect and store is specific for your application.


Access

Leveraging advanced communication protocols, data can be accessed via the user interface, built in FTP Server, or configured to be pushed to remote FTP sites or email accounts in multiple industry formats

Benefits

- ▶ Dual Trimble Maxwell 7 chipsets combined with a powerful processor provides the ultimate in tracking and processing power
- ▶ Ethernet and Wi-Fi support provide ease of access, configuration, and transfer of data. Using the built-in Web user interface gives instant access to a simple to use configuration suite
- ▶ Dual hot-swappable internal batteries with integrated charging make Alloy suitable for use in the office or remote locations, and anywhere in-between
- ▶ The intelligent design features multiple connectors and stackable housing, making Alloy easy to configure for deployment
- ▶ Designed to an IP68 certification Alloy is ready for any environment
- ▶ Includes firmware for life so it's easy to keep your Alloy reference receiver up-to-date with the latest features, enhancements and security updates, free to install from www.alloy.trimble.com





SPECIFICATIONS¹

GNSS TECHNOLOGY

- Trimble RTX World-Wide Corrections
- Advanced Trimble dual Maxwell™ 7 GNSS chipset provide 672 channels for simultaneous satellite tracking
- Trimble EVERESTPlus™ multipath signal rejection
- Trimble 360 receiver technology
- High precision multiple correlator for GNSS pseudorange measurements
- Spectrum Analyzer to troubleshoot GNSS jamming
- Unfiltered, unsmoothed pseudorange measurements data for low noise, low multipath error, low time domain correlation and high dynamic response
- Very low noise GNSS carrier phase measurements with <1 mm precision in a 1 Hz bandwidth
- Signal to Noise ratio reported in dB-Hz
- Proven Trimble low elevation tracking technology
- Proprietary Receiver Autonomous Integrity Monitor (RAIM) system to detect and reject degraded signals to improve position quality

SATELLITE TRACKING

- GPS: L1 C/A, L2E (L2P), L2C, L5
- GLONASS: L1 C/A² and unencrypted P code, L2 C/A and unencrypted P code, L3 CDMA
- Galileo: L1 CBOC, E5A, E5B & E5AltBOC, E6
- BeiDou: B1, B2, B3, B1C, B2A
- QZSS: L1 C/A, L1C, L1 SAIF, L1S, L2C, L5, LEX/L6³
- IRNSS: L5, S-Band
- SBAS: L1 C/A (EGNOS/MSAS), L1 C/A and L5 (WAAS)
- L-Band: Trimble RTX™

INPUT/OUTPUT FORMATS

- Correction Formats:
 - CMR, CMR+, CMRx, GAGAN, RTX, RTCM 2.x, RTCM 3.x, SDCM
- Observables:
 - RT17, RT27, BINEX, RTCM 3.x
- Position/Status I/O:
 - NMEA-0183 v2.30, GSOFF
- Up to 100 Hz Output
- 10 MHz External Frequency Input
 - Normal input level 0 to +13 dBm
 - Maximum input level +17 dBm, ±35 V DC
 - Input impedance 50 Ohms @ 10 MHz; DC blocked
- 1 PPS Output
- Event Input
- Met/Tilt Sensor Support

POSITIONING PERFORMANCE

Differential Positioning

Code differential GNSS positioning ⁴	
Horizontal	0.25 m + 1 ppm RMS
Vertical	0.50 m + 1 ppm RMS

SBAS differential positioning accuracy⁵

Horizontal	0.50 m RMS
Vertical	0.85 m RMS

Static GNSS Surveying⁴

High Accuracy Static	
Horizontal	3 mm + 0.1 ppm RMS
Vertical	3.5 mm + 0.4 ppm RMS

Static & Fast Static

Horizontal	3 mm + 0.5 ppm RMS
Vertical	5 mm + 0.5 ppm RMS

Real Time Kinematic Surveying⁴

Single Baseline < 30km	
Horizontal	8 mm + 1 ppm RMS
Vertical	15 mm + 1 ppm RMS

Networked RTK⁶

Horizontal	8 mm + 0.5 ppm RMS
Vertical	15 mm + 0.5 ppm RMS

Initialization time typically <10 seconds
 Initialization reliability typically >99.9%

COMMUNICATION

- Serial Ports:
 - Two 9-pin Male
 - Two 7-pin Lemo
- USB: one Mini-B USB 5-pin / RDNIS (Device and Host modes)
- Ethernet: one RJ45 (Full-duplex, auto-negotiate 100Base-T)
 - HTTP, HTTPS, TCP/IP, IPv4 / IPv6, UDP, FTP, NTRIP Caster, NTRIP Server, NTRIP Client
 - Proxy server, Routing table, NTP Server, NTP Client support
 - Email Alerts and File Push
- WiFi: 802.11 b/g, access point and client mode, WPA/WPA2/WEP64/WEP128 encryption
- Bluetooth⁷: Integrated 2.4 GHz Bluetooth; supports 3 simultaneous connections

1 Specifications subject to change without notice.

2 L2 C/A on GLONASS-M satellites.

3 LEX / L6 supported on QZSS Block I satellites.

4 Accuracy may be subject to degradation by multipath interference, obstructions, satellite geometry and atmospheric conditions. Always follow recommended survey practices.

5 Depends on WAAS/EGNOS system performance.

6 Networked RTK PPM values are reference to the closest physical base station.

7 Bluetooth type approvals are country specific.

DATA LOGGING

Storage Capacity:	
Onboard Memory (Journaling)	up to 24 GB ⁸
External Memory ⁹	greater than 1 TB
Maximum Data Logging Rate	100 Hz
Maximum Combined Data Logging Rate	188 Hz
File Durations	1 minute to continuous
Storage Sessions	12 concurrent independent sessions with dedicated memory pooling
File Formats	T02, T04, BINEX, RINEX v2.x/3.0x, Google Earth KML/KMZ
File Naming Conventions	Multiple
Data Retrieval and transfer	HTTP, FTP Server, USB
Events	Definable file protection on events

PHYSICAL SPECIFICATIONS

Alloy receiver dimensions (L x W x H) 20.98 cm x 21.36 cm x 7.62 cm
(8.41 in x 8.26 in x 3 in)

Alloy receiver dimensions
with brackets attached (L x W x H) 26.77 cm x 21.36 cm x 8.3 cm
(8.41 in x 10.54 in x 3.27 in)

Weight 2.34 kg (5.17 lbs)

ENVIRONMENT

Operating Temperature^{10,11} -40 °C to +65 °C (-40 °F to +149 °F)

Storage temperature -40 °C to +80 °C (-40 °F to +176 °F)

Humidity 100% condensing

Shock

 Operating 40 g per MIL-STD-810G Table 5.16.6-VII

 Non-Operating 75 g per MIL-STD-810G Table 5.16.6-VII

 Designed to survive 1 m bench drop

Vibration

 Operating MIL-STD-810G Fig. 5.14.6C-1 Category 4

 Ingress protection IP68 Certified per IEC-60529 - waterproof/dustproof (1 m submersion for 1 hr)

USER INTERFACE

- Front Panel Display
 - 4-line x 32 character reversible OLED display
 - 7 button input configuration
 - Adjustable LED backlighting
- Multiple language support for front panel and web UI - Chinese, Dutch, English, Finnish, French, German, Italian, Japanese, Norwegian, Polish, Portuguese, Russian, Spanish, Swedish
- Web User Interface: Allows remote configuration, data retrieval, and firmware updates over HTTPS/HTTP

ANTENNA SUPPORT

Output Voltage	5 V DC nominal
Maximum output current	150 mA
Maximum cable loss	12 dB
Recommended antennas	Trimble Zephyr 3 Geodetic, Trimble GNSS-Ti v2 Choke Ring, Trimble GNSS Choke Ring

SECURITY

- HTTP login
- HTTPS/SSL
- Programmatic Interface authentication
- NTRIP
- IP Filtering

ELECTRICAL

- Power over Ethernet (PoE) 802.3af (Type 1), 802.at (Type 2)
- 10.8 to 28.0 V DC input on 2 Lemo ports
 - User-configurable power-on voltage
 - User-configurable power-down voltage
- User-configurable 12 V DC power output on serial port #2
- Integrated dual hot-swappable smart batteries (7.4 V, 7800 mA-hr, Li-Ion batteries) with up to 15 hours of continuous operation
- Seamless switching between external/internal power sources
- Configurable minimum input voltage for battery charging
- Integrated battery charging circuitry
- Power Consumption – 3.8 W or higher, dependent on user settings

REGULATORY COMPLIANCE

- FCC Part 15 (Class B device), CISPR 32, 24
- RED CE Mark
- RCM
- UN 38.3 – ST/SG/AC.10/27/Add.2 Rev.5 (Li-Ion battery)
- IEC 62133(Ed.2) and EN 62133: 2013 (Li-Ion battery)
- RoHS, China RoHS, WEEE

⁸ Trimble's highly efficient T02 data logging format makes this equivalent to 32 GB to 55 GB for competitive receivers.

⁹ Solid state drives are recommended for optimal performance.

¹⁰ Operating temperature when connected to external DC supply. To protect the removable Li-Ion batteries from extreme temperatures, the battery charger only operates from 5 °C to 35 °C (41 °F to 95 °F).

¹¹ If operated only with batteries and no external DC supply, operating temperature is -20 °C to +55 °C (-4 °F to +131 °F).



Alloy GNSS REFERENCE RECEIVER

Contact your local Trimble Authorised Distribution Partner for more information

NORTH AMERICA
Trimble Inc.
10368 Westmoor Dr
Westminster CO 80021
USA

EUROPE
Trimble Germany GmbH
Am Prime Parc 11
65479 Raunheim
GERMANY

ASIA-PACIFIC
Trimble Navigation
Singapore PTE Limited
3 HarbourFront Place
#13-02 HarbourFront Tower Two
Singapore 099254
SINGAPORE

© 2018–2021, Trimble Inc. All rights reserved. Trimble and the Globe & Triangle logo are trademarks of Trimble Inc., registered in the United States and in other countries. Alloy, EverestPLUS, RTX and Sentry are trademarks of Trimble Inc. The Bluetooth word mark and logos are owned by the Bluetooth SIG, Inc. and any use of such marks by Trimble Inc. is under licence. Wi-Fi is a registered trademark of the Wi-Fi Alliance. All other trademarks are the property of their respective owners. PN 022506-243F (10/21)